

## EPA TSCA Title VI CERTIFICATION APPLICATION FORM

Applicant:
Address:
Location where the certified products are produced (if not the same as above):
Contact person:
Email address:
Name and address of the report header (if different from the applicant)
Name: -
Address: -
Name and address of "invoice to" Company (if different from the applicant)
Name: -
Address: -

### Payment Information if different from above:

Name:		
Address:		
E-mail:		
Contact Person:	Tel:	Fax:

### Audit Information:

<input checked="" type="checkbox"/> Initial Certification applicable for one single thickness (correlation establishment is based on one single thickness) Product Thickness:
<input checked="" type="checkbox"/> Initial Certification applicable for product thickness grouping (correlation establishment is based on the representative thickness) Product Thickness Grouping Information:  Representative Thickness:
<p>Note 1: For product thickness grouping, select the thickest (or the thinnest) thickness (5 lots) as representative thickness for correlation establishment of a group of 1 to 4 thicknesses. Select the thickest (or the thinnest) thickness (5 lots) and the thinnest (or the thickest) thickness (1 lot) as representative thicknesses for correlation establishment of a group of 5 to 8 thicknesses. Select the thickest (or the thinnest) thickness (5 lots), the thinnest (or the thickest) thickness (1 lot) and intermediate thicknesses (1 lot per thickness) based on the "4 select 1" principle as representative thicknesses for correlation establishment of a group of more than 6 thicknesses.</p> <p>Note 2: Additional documents such as (1) Service Agreement, (2) Declaration of Engagement, (3) Certification Confirmation Letter and (4) Factory Declaration Letter are to be filled by applicant for initial certification. <b>Incomplete or incorrect information supplied on this form and additional documents may result in rejection of the application or subsequent withdrawal of the certificate granted.</b></p>
<input type="checkbox"/> Quarterly Visit
<input type="checkbox"/> Amendment, please specify:

### Product Information:

Product Description:
Product Category and Thickness: (mm)
<input type="checkbox"/> Hardwood Plywood-Veneer Core, HWPW-VC <input type="checkbox"/> Hardwood Plywood-Composite Core, HWPW-CC <input type="checkbox"/> Particleboard, PB <input type="checkbox"/> Medium Density Fiberboard, MDF (> 8mm) <input type="checkbox"/> Thin Medium Density Fiberboard, Thin MDF (≤ 8mm)
Certificate Requirement:
EPA TSCA Title VI Compliant
Product Usage: <input type="checkbox"/> Yes / <input type="checkbox"/> No
Product Line Information:

**Test Service requested: please fill in your test standard(s) or item(s).**

TSCA (Correlation establishment applicable for initial certification/ extension scope):		
<input type="checkbox"/> ASTM D6007-14 Product type test		
The below situation is applicable only if manufacturer has subcontracted the small scale test (ASTM D5582-14) to SGS :		
<input type="checkbox"/> ASTM D6007-14 & ASTM D5582-14 (      days is required for conditioning. If not specified, SGS assumes it to be 7 days)		
<b>* Remarks: The below entries must not be identical, otherwise tests could not be performed</b>		
Thickness:		
A. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
B. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
C. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
D. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
E. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
* All samples for testing must be manufactured within 25 days		
Sample size		
Panel Type / Method	ASTM D6007-14	ASTM D5582-14
Hardwood Plywood	40 cm x 39.5 cm (9 pcs)	70±2 mm x 127±2 mm (8 pcs)
Particleboard Flooring Panels, Industrial Particleboard Panels, Industrial Hardwood Plywood Panels	27 cm x 26.5 cm (9 pcs)	(Theoretical Surface area: 1422.4 cm <sup>2</sup> for 2-sided)
MDF	21 cm x 20.5 cm (9 pcs)	
CARB/ TSCA (Non-correlation establishment applicable for quarterly visit):		
<input type="checkbox"/> ASTM D6007-14 Product type test		
The below situation is applicable only if manufacturer has subcontracted the small scale test (ASTM D5582-14) to SGS :		
<input type="checkbox"/> ASTM D6007-14 & ASTM D5582-14 (      days is required for conditioning. If not specified, SGS assumes it to be 7 days)		
<b>* Remarks: The below entries must not be identical, otherwise tests could not be performed</b>		
Thickness:		
A. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
B. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
C. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
D. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
E. Lot no. :	Manufacturing Date	(year) (Month) (Day) (Shift) (Production line)
Sample size:		
Panel Type / Method	ASTM D6007-14	ASTM D5582-14
Hardwood Plywood	40 cm x 39.5 cm (9 pcs)	70±2 mm x 127±2 mm (8 pcs)
Particleboard Flooring Panels, Industrial Particleboard Panels, Industrial Hardwood Plywood Panels	27 cm x 26.5 cm (9 pcs)	(Theoretical Surface area: 1422.4 cm <sup>2</sup> for 2-sided)
MDF	21 cm x 20.5 cm (9 pcs)	

Remark: Samples for testing will not be returned by SGS.

Certificate Pick Up :  Self-pick up  Express

Certificate delivery information (if different from above)

Postal Address:

Contact person:

Phone number:

E-mail:

Quotation Required:  Yes/  No

Previous Report No. (if applicable):

Previous Certificate No. (if applicable):

Please Signify Your Acceptance By Authorized Signature & Company Chop

Date:

(Enclosed General Conditions of Service Printed Overleaf)